



Finish

Premixed cement-based sprayable thin plaster for walls and ceilings in interior and exterior conditions

PRODUCT

FINISH is a high quality, specially blended premixed thin plaster for finishing walls and ceilings. It is a cement-based and water resistant plaster which can be used in interior and exterior conditions. The plaster can be sprayed to give a spray-textured finish or manually trowelled for a smooth finish.

FINISH can be used on concrete, lightweight concrete blockworks rendered and painted surfaces. A hardened plastered surface can be painted or wallpapered.

TECHNICAL DATA AND PHYSICAL PROPERTIES

Colour	White / Grey
Binder	Ordinary Portland Cement
Filler	Graded limestone powder
Additives	Water soluble polymers to improve consistency, workability, water retention and adhesion.
Max. aggregate size	0.5 mm
Density	1.4 kg/litre (dry) ; 1.6 kg/litre (wet)
Adhesion to concrete	> 0.8 N/mm ²
Pot life	3 hours
Coat thickness	1 - 3 mm per coat
Consumption	Approx. 1.2 kg/m ² /mm thick
Water demand	Approx. 32% or 8.0 litres/25 kg bag - FINISH GREY Approx. 34% or 8.5 litres/25 kg bag - FINISH WHITE

PROCEDURE

Ensure substrate is clean and sound. Remove loose particles, grease and traces of foreign materials that may affect adhesion. Where necessary, especially on hot and high absorbent substrates, dampen surface before application of the plaster.

Mix product with the required amount of clean water. Mix thoroughly with a mechanical mixer until mixture is homogeneous. Allow mixture to stand for 10 minutes for the additives to dissolve. Mix again and the plaster is ready for use. Application is done manually with steel trowel/spatula or sprayed with a suitable spray machine. No further addition of water is allowed to unused plaster that has exceeded its pot life or has begun to set.

For thicker applications with several layers, the layer underneath must be hardened and dry before applying the subsequent layer.

STORAGE AND PACKING

FINISH is delivered in 25 kg bags. Storage life is 6 months if product is stored in sheltered and dry place.

*Note: Because it is not possible to give specific instructions for the various site conditions or to control the applications, the information on this Technical Data Sheet is for general guidance only. Eastern Pretech Pte Ltd reserves the rights to amend the contents of the data sheet at its sole discretion.

(May '11)